



On Top of your pressure Tank

Access Tank Cover - Circular Cover Type HLSD-2

Application

Outward opening manhole cover type HLSD-2 is used on top of pressurized tanks and containers where closeable means of access to the interior of the vessel is required. HLSD-2 is approved and can be used on pressure vessels according to PED 97/23/EC.

Working principle

HLSD-2 is secured in the closed position by swingbolts, which, together with the seal in the cover, ensure complete tightness. The cover is attached to the frame by a rigid hinge, giving exact location of the cover in the closed position and designed to stop the cover at an angle of 20-30° beyond the vertical position when opening.

Standard design

- HLSD-2 is designed according to Merkblätter AD 2000 newest edition.
- HLSD-2 is designed for mounting in pressure vessels until hazard category IV.
- HLSD-2 is designed for fluid group 1 and 2.
- HLSD-2 is not pressure tested and must be tested as a part of the pressure vessel.
- HLSD-2 has from 4 up to 14 swingbolts subject to size, pressure and temperature.
- The seal between cover and frame is located in the cover.



HLSD-2, Manhole Cover.

Materials

Product wetted steel parts: 1.4404 (AISI 316L)

Other steel parts: 1.4301 (AISI 304).

Certificates:

- Incl. inspection certificate 3.1 according to EN 10204 for product wetted steel parts.
- Incl. EC unit verification module G according to PED 97/23/EC.
- Incl. FDA declaration § 177.2600 for seal material (except FPM seal).

Seal: EPDM, FPM, Silicone, FEP covered silicone, FEP covered viton, PFA covered silicone.
For recommended max. temperatures, please see paragraph concerning technical information.

Finish: Standard surface finish: Semi bright. Outside Ra 1.6, inside Ra 0.8.
Other surface finishes available as option.

Note! Weldings are not treated.

Technical Data

Max. allowable pressure PS (bar):	According to selection table.
Min. allowable negative pressure PS (bar):	Full vacuum.
Max. test pressure P _{test} (bar):	According to selection table.
Temperature range:	-10 °C to + 250 °C (-50 °F to 482 °F)

Sizes

Internal diameters of frame:

200 mm, 300 mm, 400 mm, 450 mm, 500 mm and 600 mm (7.87 inch, 11.81 inch, 15.75 inch, 17.72 inch, 19.68 inch and 23.62 inch).

Options

- A. Spring to assist opening.
- B. Arrangement for securing cover in open and closed position.
- C. Bracket for indication unit.
- D. Handle in stainless steel.
- E. Guide for cover for vertical installation. Please define positioning of the hinge (right or left hand side).
- F. Sight glass DIN 28120.
- G. Sight glass DIN 11851.
- H. Safety grid.
- I. Special surface finish.
- J. Frame height G = 300 mm (11.82 inch).
- K. Seal of Q (silicone), FPM (viton), FEP covered silicone, PFA covered silicone, FEP covered viton.
- L. Conical frame, different frame thickness and frame height available on request.

Ordering

Please state the following when ordering:

- Cover size.
- Max. pressure and corresponding temperature.
- Max. temperature and corresponding pressure.
- Optional extras.

ESE00694EN 0804

The information contained herein is correct at the time of issue,
but may be subject to change without prior notice.

How to contact Alfa Laval

Contact details for all countries
are continually updated on our website.
Please visit www.alfalaval.com to
access the information direct.